



TT - Turntable Model



Accordion Bellows Skirting



Hinged Maintenance Bars



Semi-Live Portability L2K Only



Cart Portability L2K / L3K Only



Contoured Platform Corners for Operator Safety

Bishamon 
ON-DEMAND

***Bishamon On-Demand Group ships in 48 hours or less!**

Standard Optimus® Lift Tables and Standard EZ Loader® Automatic Pallet Positioners are included in this product group

Adding options may affect delivery. Contact Bishamon for a complete copy of the On-Demand Program.

Warranty:

Bishamon Industries Corporation warrants its products to be free from defects in material and workmanship for a period of one (1) year from the date of initial shipment.

This warranty shall not apply to any misuse, mishandling, accident, shipping, alteration, or unauthorized repair of any Bishamon product or part. For complete details of warranty, please contact Bishamon at: 800-358-8833.

DISTRIBUTED BY:



Bishamon

Bishamon Industries Corporation
5651 East Francis Street
Ontario, California 91761-3601
Ph: 800-358-8833 US & Canada
909-390-0055 Outside US/CN
Fax: 800-700-0492

www.bishamon.com

BIC-OPT-07-14

Bishamon

OPTIMUS® LIFT TABLES

Bishamon's Next Generation of Quality Lift Tables Shipped to You in 48 Hours!*

Bishamon 
ON-DEMAND



Lift2K®



Lift3K™



Lift5K™

Experience Industry's "Best Engineered" Line of Lift Tables



SHIPS IN 48 HOURS

Learn More at: bishamon.com

Working Harder To Make Your Job Easier

Working Harder To Make Your Job Easier



Optimus® LK Series Standard Features

- Complies with ANSI MH 29.1:2012 "Safety Requirements for Industrial Scissors Lifts"
- 115 volt operator control system
- 230 and 480 volt power units have a 24 VAC operator control system
- Flow limiting valves
- Pressure compensated flow control at power unit
- Hinged maintenance bars
- Self-lubricating, maintenance free bushings at all pivot points
- Unitized, compact, internal power unit and reservoir combination
- Continuous axles at rollers
- Cylinders are heavy duty with chrome plated rods
- Contoured platform corners for operator safety - see photo back page
- Easy view hydraulic reservoir
- All electrical components are UL or CSA Certified
- Intuitive and user-friendly plug and play controls
- Clean, accessible, maintenance friendly design
- Durable powder coated finish
- Entrapped rollers in base frame and platform for added stability



Optimus® LK Series models listed below are part of the Bishamon "On-Demand" Program and are Guaranteed to ship in 48 hours



(Qty 1-5 Units)



Optimus Lift2K® Series

Model	Travel (in)	Capacity (lbs)	Platform Size (in)	Height (in)		Voltage	Approx. Up Time (Sec)	Approx. Dn. Time (Sec)	Approx Shp Weight
				Lowered	Raised				
L2K-2848	30	2,000	28 x 48	8.50	38.50	115 VAC	24	12	469
L2K-3648	30	2,000	36 x 48	8.50	38.50	115 VAC	24	12	490
L2K-TT	30	2,000	43 Dia. Rotating	11.50	41.50	115 VAC	24	12	540

L2K-FC Foot operated controls with guard (Hand control standard)

Optimus Lift3K™ Series

Model	Travel (in)	Capacity (lbs)	Platform Size (in)	Height (in)		Voltage	Approx. Up Time (Sec)	Approx. Dn. Time (Sec)	Approx Shp Weight
				Lowered	Raised				
L3K-2848	34	3,000	28 x 48	8.63	42.63	115 VAC	25	12	530
L3K-3648	34	3,000	36 x 48	8.63	42.63	115 VAC	25	12	560
L3K-TT	34	3,000	43 Dia. Rotating	11.75	45.75	115 VAC	25	12	680

L3K5K-FC Foot operated controls with guard (Hand control standard)

Optimus Lift5K™ Series

Model	Travel (in)	Capacity (lbs)	Platform Size (in)	Height (in)		Voltage	Approx. Up Time (Sec)	Approx. Dn. Time (Sec)	Approx Shp Weight
				Lowered	Raised				
L5K-3256	39.25	5,000	32 x 56	8.75	48	115 VAC	50	24	730
L5K-4872	39.25	5,000	48 x 72	8.75	48	115 VAC	50	24	1030

L3K5K-FC Foot operated controls with guard (Hand control standard)

Optimus® LK Series models listed below along with most options and accessories are not part of the Bishamon "On-Demand" Program but will generally ship within 1-2 weeks.



Optimus Lift2K® Series

Model	Travel (in)	Capacity (lbs)	Platform Size (in)	Height (in)		Voltage	Approx. Up Time (Sec)	Approx. Dn. Time (Sec)	Approx Weight
				Lowered	Raised				
L2K-TT4444	30	2,000	44 X 44 Rotating	11.50	41.50	115 VAC	24	12	630
L2K-TT4448	30	2,000	44 X 48 Rotating	11.50	41.50	115 VAC	24	12	640
L2K-TT4848	30	2,000	48 X 48 Rotating	11.50	41.50	115 VAC	24	12	650

Options & Accessories for L2K Series

L2K-FC	Foot operated controls with guard (Hand control standard)
L2K3K-ABS	Accordion bellows skirting
EZ-SLP	Semi-live portability for moving unloaded lift (2 wheels and dolly handle)
EZ-CART	Cart portability with 2 swivel wheels and 2 rigid wheels (adds 7" to lowered and maximum raised heights)

Optimus Lift3K™ Series

Model	Travel (in)	Capacity (lbs)	Platform Size (in)	Height (in)		Voltage	Approx. Up Time (Sec)	Approx. Dn. Time (Sec)	Approx Shp Weight
				Lowered	Raised				
L3K-SPECIAL	34	3,000	(28x48 to 48x72 in 2" increm.)	8.63	42.63	115 VAC	25	12	660
L3K-TT4444	34	3,000	44 X 44 Rotating	11.75	45.75	115 VAC	25	12	770
L3K-TT4448	34	3,000	44 X 48 Rotating	11.75	45.75	115 VAC	25	12	780
L3K-TT4848	34	3,000	48 X 48 Rotating	11.75	45.75	115 VAC	25	12	790

Options & Accessories for L3K Series

L3K5K-FC	Foot operated controls with guard (Hand control standard)
L2K3K-ABS	Accordion bellows skirting
EZ-CART	Cart portability with 2 swivel wheels and 2 rigid wheels (adds 7" to lowered and maximum raised heights)
LK-230PU-1	230 VAC, 1 Phase motor with 24V controls: no change in up time
LK-230PU-3	230 VAC, 3 Phase motor with 24V controls: decreases up time to 14 seconds
LK-480PU	480 VAC, 3 Phase motor with 24V controls: decreases up time to 14 seconds

Optimus Lift5K™ Series

Model	Travel (in)	Capacity (lbs)	Platform Size (in)	Height (in)		Voltage	Approx. Up Time (Sec)	Approx. Dn. Time (Sec)	Approx Shp Weight
				Lowered	Raised				
L5K-SPECIAL	39.25	5,000	(32x56 to 48x84 in 2" increm.)	8.75	48	115 VAC	50	24	1075
L5K-TT	39.25	5,000	43 Dia. Rotating	11.87	51.12	115 VAC	50	24	870
L5K-TT4444	39.25	5,000	44 X 44 Rotating	11.87	51.12	115 VAC	50	24	1000
L5K-TT4448	39.25	5,000	44 X 48 Rotating	11.87	51.12	115 VAC	50	24	1015
L5K-TT4848	39.25	5,000	48 X 48 Rotating	11.87	51.12	115 VAC	50	24	1030

Options & Accessories for L5K Series

L3K5K-FC	Foot operated controls with guard (Hand control standard)
L5K-ABS	Accordion bellows skirting
LK-230PU-1	230 VAC, 1 Phase motor with 24V controls: no change in up time
LK-230PU-3	230 VAC, 3 Phase motor with 24V controls: decreases up time to 14 seconds
LK-480PU	480 VAC, 3 Phase motor with 24V controls: decreases up time to 14 seconds

Some options and accessories are not field installable - consult sales

Note: Not all options are compatible - consult sales

Option and accessory pricing applies to options purchased with an LK-Series lift table at time of order